



NEW FROM SOLAX

Rapid Shutdown Device 1 connection

XRSD-1C

Description

Prioritizing safety and rapid shutdown capabilities, the XRSD series offers a sophisticated module-level solution that guarantees the smooth functioning of both new and existing PV systems. Once activated by the SolaX Transmitter—XRSD-Core Kit, the XRSD modules ensure your connected PV system remains operational.

In case of emergencies, you have multiple shutdown options: either remotely control each individual panel through the SolaX cloud, toggle the AC breaker on the Transmitter, or engage the E-STOP button. This versatility makes the XRSD system a reliable safety measure for quick deactivation of your PV system as needed.

Note: To achieve rapid shutdown, please use with the TRANSMITTER KIT (Model: XRSD-CORE KIT).

Features

- 1 Module-level rapid shutdown
- 2 Module-level monitoring (optional)
- 3 Max. PV input current 20A: Compatible with all PV panels
- 4 Ultra-low signal noise, won't trigger inverter's AFCI.
- 5 Lower power consumption and wider operating voltage range
- 6 Easy to install and maintain with standard MC4 connector panels
- 7 Compatible with all SolaX inverters as well as other inverter brands
- 8 IP68 with unrivaled reliability

info@solaxpower.com
service@solaxpower.com



Contact Us for More Informations

www.solaxpower.com
AU: +61 1300 476529
DE: +49 6142 4091664

Global: +86 571-56260008
UK: +44 2476 586998
NL: +31 (0) 852 737932



Rapid Shutdown Device 1 connection

XRSD-1C

ELECTRICAL DATA	
Input voltage range [V]	8-80
Output voltage range [V]	8-80
Max. PV input current [A]	20
Max. short circuit current [A]	26
Recommended fuse rating [A]	30
Maximum system voltage [V]	1500
MECHANICAL	
Dimensions* (W x H x D) [mm]	120 x 33 x 16
Weight [g]	350
Input connectors	MC4 (Standard)
Input cable length [m]	0.2
Output connectors	MC4 (Standard)
Output cable length [m]	1.2
Communication type	PLC
ENVIRONMENT LIMIT	
Protection class	IP68 / NEMA6P
Operating temperature range[°C]	-40°C to +85°C (-40°F to +185°F)
COMPLIANCE	
Safety	NEC 2017&2020 (690.12); UL1741; CSA C22.2 No. 330-17; IEC/EN62109-1
EMC	FCC Part15; ICES-003; IEC/EN 61000-6-1/-2/-3/-4

* Note: without cables and connectors